



**Save up to 20%
of your HD Space**

**The 1st Camera made
for the DVR Industry**

DD-540NDV



FEATURES

- Day & Night
- Electronic IRIS
- 540TV Lines of Horizontal Resolution
- Privacy Function
- 3Axis built-in 120mm/4.7in Dome Housing
- High Sensitivity
- DNR (Digital Noise Reduction)
- Controlled by OSD Menu

SPECIFICATIONS

ITEM	NTSC		PAL		
	AC24V / DC12V	DC12V	AC24V / DC12V	DC12V	
Power Source	215mA(AC24V) / 250mA(DC12V)	160mA	215mA(AC24V) / 250mA(DC12V)	160mA	
C C D	Total Pixels	811(H) X 508(V)	795(H) X 596(V)		
	Effective Pixels	768(H) X 494(V)	752(H) X 582(V)		
	Size	1/3 inch interline transfer CCD			
Scanning System	2:1 interlace				
S Y N C	Synchronization	INT/LL Selectable 0 ~ 359° (Adjustable)	INT	INT/LL Selectable 0 ~ 359° (Adjustable)	INT
	Frequency	Horizontal: 15.734 KHz Vertical: 59.94Hz		Horizontal: 15.625 KHz Vertical: 50.00Hz	
E L C T R I C	Resolution	540 TV Lines			
	Video Output	1.0Vp-p75 (Video 0.714Vp-p Sync 0.286Vp-p)		1.0Vp-p75 (Video 0.7Vp-p Sync 0.3Vp-p)	
	S/N (Y signal)	50dB (AGC Off)			
	Min. Illumination	0.3Lux / F1.2 (Color), 0.1Lux / F1.2 (B/W), 0.002Lux (Sens-up)			
A L	COLOR	ON / AUTO			
	Gain Control	OFF / LOW / MIDDLE / HIGH			
	White Balance	ATW / AWC / MANUAL (1,8000K ~ 10,5000K)			
	Electronic shutter speed	AUTO / MANUAL (1/60 ~ 1/120,000)		AUTO / MANUAL (1/50 ~ 1/120,000)	
C A L	Sens - Up	OFF / AUTO			
	O.S.D	Built-in			
	Motion Detection	ON / OFF (4 Programmable Zone)			
	DNR	OFF / LOW / MIDDLE / HIGH / (Noise Reduction)			
MIRROR	Built-in (Horizontal Image Inversion)				
Privacy Function	ON / OFF (4 Programmable Zone)				
Operating temperature/Humidity	-10°C ~ +50°C/14°F -122°F / 30 ~ 90% RH				
Weight	0.630g / 1.4lb				

Authorized Dealer: