



IPV-200

FEATURES

- Dynamic IP Support with DDNS Service
- Stable and Compact Sized 1 CH Video Web Server
- High Frame Rate with Superior Video Quality (MAX. 30fps / M-JPEG)
- Various Image Size Support
- Powerful PTZ Function with Various Protocol
- 1CH Loop-Through Video Output for CCTV Monitor, VCR, DVR, etc.
- Pure WEB based Monitoring Solution
- Simultaneous 16CH Remote Recording with Client Software (i-Pro)
- Remote System management: Configuration and Upgrade
- Digital Input 2 / Output 2 (Optional Alarm In/Out Module Required)
- SDK (Software Development Kit)

SPECIFICATIONS

ITEMS		IPV-200
Hardware:	CPU	32Bit RISE Processor
	OS	Embedded Linux
	Flash Memory	8MB
	RAM	16MB
Viewer:		Web Brower Based Monitoring
Network:	Protocol	TCP/IP, HTTP, FTP, SMTP, PPP, UDP and More
	Interface	0/100 base-T Ethernet(RJ-45)
Compression:	Algorithm	M-JPEG
	Rate	1/10-1/1200
Video:	Input	1CH, NTSC/ PAL
	Output	1CH, NTSC/ PAL
	Size	640X480, 320X240, 160X120
	Frame Rate	30 frame/sec (320x240)
Pan/Tilt Control	Frame Rate:	RS-232C
Power:		DC12V/ 500mA
Dimension:		98(W)x27(H)x100(L)mm / 3.8(W)x1.06(H)x3.9(L)in incl. bracket
Weight:		Approx 0.150g / 0.330lb
Operating Temperature:		0°C ~ 40°C (32°F~104°F)

Authorized Dealer: